

屋内照明器具特性

品番 (品名)	LGB10830	
光源	LLD5000LCC1 ×1	1140.0 1m
管理番号	K0190434(0)DR1	
BZ分類	BZ3	

器具効率	96%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		下方光束 95%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
		室指数	照明率 (×0.01)																ZCM	
保守率	良	0.67	0.6	62	52	45	41	60	51	45	41	58	50	44	40	56	49	44	40	38
	中	0.63	0.8	71	62	56	51	70	62	56	51	68	60	55	51	66	59	54	51	49
	否	0.56	1.0	77	69	63	59	76	68	63	59	74	67	62	58	71	66	61	58	56
			1.25	83	75	70	66	81	74	69	65	79	73	68	65	76	71	67	64	62
下方投影面積	cm ²		1.5	86	79	74	70	84	78	74	70	82	77	73	69	79	75	72	69	66
等価発光面積	cm ²		2.0	90	85	81	77	89	84	80	76	86	82	79	76	84	80	77	75	72
取付高さ	器具間隔最大限		2.5	93	88	85	81	92	87	84	81	89	85	82	80	86	84	81	79	76
	横方向 (A)	縦方向 (B)	3.0	95	91	87	85	93	90	87	84	91	88	85	83	88	86	84	82	79
Hm	1.26Hm	1.26Hm	4.0	97	94	91	89	96	93	90	88	93	91	89	87	91	89	87	85	83
			5.0	98	96	94	91	97	95	93	91	94	93	91	89	92	90	89	88	85
			7.0	100	98	96	95	99	97	95	94	96	95	93	92	94	93	91	90	88
			10.0	101	100	98	97	100	99	97	96	97	96	95	94	95	94	93	93	90

