

屋内照明器具特性

品番 (品名)	LGB10830		
光源	LLD5020LCC1 ×1	1085.0 1m	
管理番号	K0190436(0)DR1		
BZ分類	BZ1		

器具効率	79%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	79%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良 0.67	0.6	67	62	59	57	66	62	59	57	65	61	59	57	64	61	58	57	56	
	中 0.63	0.8	72	68	65	63	71	67	65	63	70	67	64	63	69	66	64	62	61	
	否 0.56	1.0	74	71	68	67	74	71	68	66	73	70	68	66	71	69	67	66	65	
下方投影面積	cm ²	1.25	77	74	72	70	76	73	71	70	75	73	71	69	74	72	70	69	68	
		1.5	78	76	74	72	78	75	73	72	76	74	73	71	75	73	72	71	70	
等価発光面積	cm ²	2.0	80	78	77	75	80	78	76	75	78	77	75	74	77	76	75	74	72	
		2.5	82	80	79	77	81	79	78	77	79	78	77	76	78	77	76	75	74	
取付高さ	器具間隔最大限		3.0	82	81	80	79	82	80	79	78	80	79	78	77	79	78	77	76	75
H _m	横方向 (A)	縦方向 (B)	4.0	83	82	81	81	82	82	81	80	81	80	80	79	80	79	78	78	76
	0.41H _m	0.41H _m	5.0	84	83	82	82	83	82	82	81	81	81	81	80	80	80	79	79	77
			7.0	85	84	84	83	84	83	83	83	82	82	82	81	81	80	80	80	78
			10.0	85	85	85	84	84	84	84	84	83	82	82	82	81	81	81	81	79

