

# 屋内照明器具特性

品番 (品名)	LGB10832				
光源	LLD2000LCE1 ×1                      531.0 lm				
管理番号	K0176328 (0) DR1				
BZ分類	BZ4				

器具効率	87%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	6%	室指数	照明率 ( X0.01 )																ZCM	
下方光束	81%																			
保守率	良 中 否 0.67 0.63 0.56	0.6	50	40	34	29	49	39	33	29	46	38	33	29	44	37	32	28	26	
		0.8	59	50	44	39	58	49	43	39	55	47	42	38	52	46	41	37	35	
		1.0	65	57	51	46	64	56	50	46	60	54	49	45	58	52	48	44	42	
		1.25	70	63	57	53	69	62	56	52	65	60	55	51	62	58	54	50	48	
下方投影面積	c m <sup>2</sup>	1.5	74	67	62	58	72	66	61	57	69	64	59	56	66	61	58	55	52	
		2.0	78	73	68	65	77	71	67	64	73	69	65	62	70	67	64	61	58	
取付高さ	器具間隔最大限		2.5	81	76	72	69	79	75	71	68	76	72	69	67	73	70	67	65	62
	横方向 (A)	縦方向 (B)	3.0	83	79	75	72	81	77	74	71	78	75	72	70	75	72	70	68	65
H m	1.32 H m	1.32 H m	4.0	85	82	79	77	84	81	78	76	80	78	76	74	77	75	73	72	68
			5.0	87	84	82	79	85	83	80	78	82	80	78	76	79	77	75	74	70
			7.0	88	86	84	83	87	85	83	81	83	82	80	79	80	79	78	77	73
			10.0	90	88	87	85	88	87	85	84	85	84	82	81	82	81	80	79	75

