

屋内照明器具特性

品番 (品名)	LGB10832									
光源	LLD5000LCC1 ×1					1140.0 lm				
管理番号	K0190437(0)DR1									
BZ分類	BZ3									

器具効率	97%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 96%	10%				10%				10%				10%			
室指数	照明率 (×0.01) ZCM																			
保守率	良	0.67	0.6	62	52	45	41	61	51	45	41	59	50	45	40	57	49	44	40	39
	中	0.63	0.8	72	62	56	52	70	62	56	51	68	61	55	51	66	59	55	51	49
	否	0.56	1.0	78	69	64	59	76	69	63	59	74	67	62	58	72	66	62	58	56
			1.25	83	76	70	66	82	75	70	65	79	73	69	65	77	72	68	64	62
下方投影面積			1.5	86	80	75	70	85	79	74	70	82	77	73	69	80	75	72	69	67
	等価発光面積		2.0	91	85	81	77	89	84	80	77	87	82	79	76	84	81	78	75	73
取付高さ	器具間隔最大限		2.5	93	89	85	82	92	88	84	81	89	86	83	80	87	84	81	79	77
	横方向 (A)	縦方向 (B)	3.0	95	91	88	85	94	90	87	84	91	88	85	83	89	86	84	82	79
Hm	1.26Hm	1.25Hm	4.0	97	94	92	89	96	93	91	88	94	91	89	87	91	89	87	86	83
			5.0	99	96	94	92	97	95	93	91	95	93	91	89	93	91	89	88	85
			7.0	100	98	97	95	99	97	96	94	97	95	94	92	94	93	92	91	88
			10.0	102	100	99	98	100	99	98	97	98	97	96	95	95	95	94	93	90

