

屋内照明器具特性

品番 (品名)	LGB10832	
光源	LLD5010LCC1 ×1	1095.0 lm
管理番号	K0190438(0)DR1	
BZ分類	BZ1	

器具効率	97%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	97%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	82	76	72	70	81	76	72	70	80	75	72	69	78	74	71	69	68
	中	0.63	0.8	87	82	78	75	86	81	78	75	85	80	77	75	83	79	77	75	73
	否	0.56	1.0	90	85	82	79	89	85	82	79	88	84	81	79	86	83	80	78	77
下方投影面積	等価発光面積	cm ²	1.25	93	89	85	83	92	88	85	83	90	87	84	82	89	86	83	81	80
			1.5	95	91	88	85	94	90	87	85	92	89	86	84	90	88	85	84	82
取付高さ	器具間隔最大限		2.5	99	96	94	92	98	95	93	91	96	93	92	90	94	92	90	89	87
	横方向 (A)	縦方向 (B)	3.0	100	97	95	94	99	96	95	93	97	95	93	92	95	93	92	91	88
Hm	0.82Hm	0.81Hm	4.0	101	99	98	96	100	98	97	95	98	96	95	94	96	95	94	93	90
			5.0	102	100	99	98	101	99	98	97	99	97	96	95	97	96	95	94	91
			7.0	103	102	101	100	102	101	100	99	99	99	98	97	97	97	96	95	93
			10.0	104	103	102	101	102	102	101	100	100	100	99	98	98	98	97	97	94

