

屋内照明器具特性

品番 (品名) **LGB10832**

光源 **LLD5020LCC1 ×1** **1085.0** l m

管理番号 **K0190439 (0) DR 1**

BZ分類 **BZ1**

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	79 %		壁	10 %				10 %				10 %				10 %				
		床	10 %				10 %				10 %				10 %					
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	67	62	59	57	66	62	59	57	65	61	59	57	64	61	59	57	56
	中	0.63	0.8	72	68	65	63	71	68	65	63	70	67	65	63	69	66	64	63	62
	否	0.56	1.0	75	71	69	67	74	71	69	67	73	70	68	66	72	69	68	66	65
下方投影面積	c m ²	1.25	77	74	72	70	77	74	72	70	75	73	71	70	74	72	70	69	68	
		1.5	79	76	74	73	78	76	74	72	77	75	73	72	76	74	72	71	70	
等価発光面積	c m ²	2.0	81	79	77	76	80	78	77	75	79	77	76	75	77	76	75	74	73	
		2.5	82	80	79	78	81	80	78	77	80	79	77	77	78	77	77	76	74	
取付高さ	器具間隔最大限		3.0	83	81	80	79	82	81	80	79	81	80	79	78	79	78	78	77	75
	横方向 (A)	縦方向 (B)	4.0	84	83	82	81	83	82	81	81	81	81	80	80	80	79	79	78	77
H m	0.41 H m	0.41 H m	5.0	84	84	83	82	84	83	82	82	82	81	81	81	81	80	80	79	78
			7.0	85	85	84	84	84	84	83	83	83	82	82	82	81	81	81	81	79
			10.0	86	85	85	85	85	85	84	84	83	83	83	83	82	81	81	81	79

