

屋内照明器具特性	
品番 (品名)	LGB10833
光源	LLD5000LCC1 ×1 1140.0 lm
管理番号	K0190443(0)DR1
BZ分類	BZ3

器具効率	96%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	95%	室指数	照明率 (×0.01)																ZCM	
保守率	良	0.67	0.6	62	52	45	41	60	51	45	41	58	50	44	40	56	49	44	40	39
	中	0.63	0.8	71	62	56	52	70	62	56	51	68	60	55	51	66	59	54	51	49
	否	0.56	1.0	77	69	63	59	76	68	63	59	74	67	62	58	71	66	61	58	56
			1.25	82	75	70	66	81	74	69	65	79	73	68	65	76	71	67	64	62
下方投影面積	cm ²	1.5	86	79	74	70	84	78	74	70	82	77	73	69	79	75	72	69	67	
		2.0	90	85	81	77	89	84	80	77	86	82	79	76	84	80	77	75	73	
取付高さ	器具間隔最大限		2.5	93	88	85	82	91	87	84	81	89	85	82	80	86	84	81	79	76
	横方向 (A)	縦方向 (B)	3.0	95	91	87	85	93	90	87	84	91	88	85	83	88	86	84	82	79
Hm	1.26Hm	1.26Hm	4.0	97	94	91	89	95	93	90	88	93	91	89	87	90	89	87	85	83
			5.0	98	96	93	91	97	95	92	91	94	92	91	89	92	90	89	88	85
			7.0	100	98	96	95	98	97	95	94	96	94	93	92	93	92	91	90	87
			10.0	101	99	98	97	99	98	97	96	97	96	95	94	95	94	93	92	89

