

屋内照明器具特性

品番 (品名) **LGB10833**

光源 **LLD5010LCC1 ×1** **1095.0 1m**

管理番号 **K0190444 (0) DR1**

BZ分類 **BZ1**

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	95 %	床		10 %				10 %				10 %				10 %				0 %
室指数			照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	81	75	72	69	80	75	71	69	79	74	71	69	78	74	71	69	68	
	中 0.63	0.8	86	81	77	75	85	80	77	75	83	79	76	74	82	79	76	74	73	
	否 0.56	1.0	89	84	81	79	88	84	81	78	86	83	80	78	85	82	79	78	76	
下方投影面積	c m ²	1.25	92	88	84	82	91	87	84	82	89	86	83	81	87	85	82	81	79	
		1.5	93	90	87	85	92	89	86	84	91	88	85	84	89	87	85	83	81	
等価発光面積	c m ²	2.0	96	93	90	88	95	92	90	88	93	91	89	87	91	89	87	86	84	
		2.5	97	95	93	91	96	94	92	90	94	92	91	89	92	91	89	88	86	
取付高さ	器具間隔最大限		3.0	98	96	94	92	97	95	93	92	95	93	92	91	93	92	91	89	87
	横方向 (A)	縦方向 (B)	4.0	100	98	96	95	98	97	95	94	96	95	94	93	94	93	92	91	89
H m	0.81 H m	0.81 H m	5.0	100	99	98	96	99	98	97	96	97	96	95	94	95	94	93	90	
			7.0	101	100	99	98	100	99	98	97	98	97	96	96	95	95	94	92	
			10.0	102	101	100	100	101	100	99	99	98	97	97	96	96	95	92		

