

# 屋内照明器具特性

品番 (品名) **LGB16133**

光源 **LLD5010LCC1 ×1** **1095.0 1m**

管理番号 **K0190444 (0) DR1**

BZ分類 **BZ1**

| 器具効率   | 95 %            | 天井      | 80 %         |     |     |     | 70 % |     |     |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |
|--------|-----------------|---------|--------------|-----|-----|-----|------|-----|-----|----|------|----|----|----|------|----|----|----|-----|----|
|        |                 |         | 70           | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 |     |    |
| 上方光束   | 0 %             | 反射率     | 10 %         |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |
| 下方光束   | 95 %            |         | 10 %         |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 10 % |    |    |    |     |    |
|        |                 | 室指数     | 照明率 ( X0.01) |     |     |     |      |     |     |    |      |    |    |    |      |    |    |    | ZCM |    |
| 保守率    | 良               | 0.67    | 0.6          | 81  | 75  | 72  | 69   | 80  | 75  | 71 | 69   | 79 | 74 | 71 | 69   | 78 | 74 | 71 | 69  | 68 |
|        | 中               | 0.63    | 0.8          | 86  | 81  | 77  | 75   | 85  | 80  | 77 | 75   | 83 | 79 | 76 | 74   | 82 | 79 | 76 | 74  | 73 |
|        | 否               | 0.56    | 1.0          | 89  | 84  | 81  | 79   | 88  | 84  | 81 | 78   | 86 | 83 | 80 | 78   | 85 | 82 | 79 | 78  | 76 |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 92           | 88  | 84  | 82  | 91   | 87  | 84  | 82 | 89   | 86 | 83 | 81 | 87   | 85 | 82 | 81 | 79  |    |
|        |                 | 1.5     | 93           | 90  | 87  | 85  | 92   | 89  | 86  | 84 | 91   | 88 | 85 | 84 | 89   | 87 | 85 | 83 | 81  |    |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 96           | 93  | 90  | 88  | 95   | 92  | 90  | 88 | 93   | 91 | 89 | 87 | 91   | 89 | 87 | 86 | 84  |    |
|        |                 | 2.5     | 97           | 95  | 93  | 91  | 96   | 94  | 92  | 90 | 94   | 92 | 91 | 89 | 92   | 91 | 89 | 88 | 86  |    |
| 取付高さ   | 器具間隔最大限         |         | 3.0          | 98  | 96  | 94  | 92   | 97  | 95  | 93 | 92   | 95 | 93 | 92 | 91   | 93 | 92 | 91 | 89  | 87 |
|        | 横方向 (A)         | 縦方向 (B) | 4.0          | 100 | 98  | 96  | 95   | 98  | 97  | 95 | 94   | 96 | 95 | 94 | 93   | 94 | 93 | 92 | 91  | 89 |
| Hm     | 0.81Hm          | 0.81Hm  | 5.0          | 100 | 99  | 98  | 96   | 99  | 98  | 97 | 96   | 97 | 96 | 95 | 94   | 95 | 94 | 93 | 90  |    |
|        |                 |         | 7.0          | 101 | 100 | 99  | 98   | 100 | 99  | 98 | 97   | 98 | 97 | 96 | 96   | 95 | 95 | 94 | 92  |    |
|        |                 |         | 10.0         | 102 | 101 | 100 | 100  | 101 | 100 | 99 | 99   | 99 | 98 | 97 | 97   | 96 | 96 | 95 | 92  |    |

