

# 屋内照明器具特性

品番 (品名)	LGB16141				
光源	LLD5000LCC1 ×1                      1140.0 lm				
管理番号	K0190445 (0) DR1				
BZ分類	BZ3/0.9/BZ2				

器具効率	85%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	0%	室指数																			照明率 ( X0.01 )																			ZCM																		
下方光束	85%																																																									
保守率	良 中 否	0.67	0.6	5.5	4.7	4.1	3.7	5.4	4.6	4.1	3.7	5.3	4.5	4.0	3.7	5.1	4.5	4.0	3.7	3.5																																						
		0.63	0.8	6.4	5.6	5.1	4.7	6.3	5.6	5.1	4.7	6.1	5.5	5.0	4.7	5.9	5.4	5.0	4.6	4.5																																						
		0.56	1.0	7.0	6.2	5.7	5.4	6.8	6.2	5.7	5.3	6.6	6.1	5.6	5.3	6.4	6.0	5.6	5.3	5.1																																						
			1.25	7.4	6.8	6.3	6.0	7.3	6.7	6.3	5.9	7.1	6.6	6.2	5.9	6.9	6.5	6.1	5.9	5.7																																						
下方投影面積	c m <sup>2</sup>	1.5	7.7	7.1	6.7	6.4	7.6	7.1	6.7	6.3	7.4	6.9	6.6	6.3	7.2	6.8	6.5	6.2	6.1																																							
		2.0	8.1	7.6	7.3	7.0	8.0	7.6	7.2	6.9	7.8	7.4	7.1	6.9	7.6	7.3	7.0	6.8	6.6																																							
取付高さ	器具間隔最大限		2.5	8.3	7.9	7.6	7.4	8.2	7.9	7.6	7.3	8.0	7.7	7.4	7.2	7.8	7.5	7.3	7.1	7.0																																						
	横方向 (A)	縦方向 (B)	3.0	8.5	8.1	7.9	7.6	8.4	8.1	7.8	7.6	8.1	7.9	7.7	7.5	8.0	7.7	7.6	7.4	7.2																																						
H m	1.26 H m	1.26 H m	4.0	8.7	8.4	8.2	8.0	8.6	8.3	8.1	7.9	8.3	8.2	8.0	7.8	8.2	8.0	7.8	7.7	7.5																																						
			5.0	8.8	8.6	8.4	8.2	8.7	8.5	8.3	8.2	8.5	8.3	8.2	8.0	8.3	8.1	8.0	7.9	7.7	7.7																																					
			7.0	8.9	8.8	8.6	8.5	8.8	8.7	8.5	8.4	8.6	8.5	8.4	8.3	8.4	8.3	8.2	8.1	7.9																																						
			10.0	9.0	8.9	8.8	8.7	8.9	8.8	8.7	8.6	8.7	8.6	8.5	8.5	8.5	8.4	8.4	8.3	8.1																																						

