

屋内照明器具特性

品番 (品名)	LGB15337									
光源	LLD5000LCC1 ×1 1140.0 1 m									
管理番号	K0190428 (0) DR 1									
BZ分類	BZ2									

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	0 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	92 %																																																						
保守率	良 中 否	0.67	0.6	62	53	47	43	61	52	47	43	59	51	46	43	57	51	46	43	41																																			
		0.63	0.8	71	63	58	54	70	63	57	54	68	62	57	53	66	61	56	53	52																																			
			1.0	77	70	65	61	76	69	64	61	74	68	64	60	72	67	63	60	58																																			
		0.56	1.25	81	75	71	67	80	75	70	67	78	73	69	66	76	72	69	66	64																																			
下方投影面積	c m ²	1.5	84	79	74	71	83	78	74	71	81	77	73	70	79	75	72	70	68																																				
		2.0	88	84	80	77	87	83	79	76	85	81	78	76	83	80	77	75	73																																				
取付高さ	器具間隔最大限		2.5	91	87	83	81	89	86	83	80	87	84	82	79	85	83	80	78	76																																			
	横方向 (A)	縦方向 (B)	3.0	92	89	86	83	91	88	85	83	89	86	84	82	87	84	83	81	79																																			
H m	1.32 H m	1.32 H m	4.0	94	91	89	87	93	90	88	86	91	89	87	85	89	87	85	84	82																																			
			5.0	95	93	91	89	94	92	90	89	92	90	89	87	90	88	87	86	84																																			
			7.0	96	95	93	92	95	94	93	91	93	92	91	90	91	90	89	88	86																																			
			10.0	97	96	95	94	96	95	94	93	94	93	92	92	92	91	91	90	88																																			

