

屋内照明器具特性

品番 (品名)	LGB15337		
光源	LLD5010LCC1 ×1	1095.0 1m	
管理番号	K0190429 (0) DR1		
BZ分類	BZ1		

器具効率	96%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	82	77	73	71	82	76	73	71	80	76	73	71	79	75	73	71	70	
	中 0.63	0.8	87	83	79	77	87	82	79	77	85	82	79	77	84	81	78	76	75	
	否 0.56	1.0	91	86	83	81	90	86	83	81	88	85	83	81	87	84	82	80	79	
下方投影面積 等価発光面積	cm ²	1.25	93	90	87	85	93	89	86	84	91	88	86	84	89	87	85	83	82	
		1.5	95	92	89	87	94	91	89	87	92	90	88	86	91	89	87	85	84	
取付高さ	器具間隔最大限		2.5	99	96	94	93	98	96	94	92	96	94	93	91	94	93	91	90	
	横方向 (A)	縦方向 (B)	3.0	100	98	96	94	99	97	95	94	97	95	94	93	95	94	92	90	
Hm	0.83Hm	0.83Hm	4.0	101	99	98	96	100	98	97	96	98	97	95	95	96	95	94	91	
			5.0	101	100	99	98	100	99	98	97	98	97	96	96	96	95	94	92	
			7.0	102	101	100	100	100	99	99	99	98	98	97	97	97	96	96	93	
			10.0	103	102	101	101	102	101	100	100	99	99	98	98	97	97	97	94	

