

屋内照明器具特性

品番 (品名)	LGB16748		
光源	LLD5020LCC1 ×1	1085.0 lm	
管理番号	K0190427(0)DR1		
BZ分類	BZ1		

器具効率	81%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	81%	床	10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)	ZCM																	
保守率	良	0.67	0.6	68	64	61	59	68	64	61	59	67	63	60	59	66	63	60	58	58
	中	0.63	0.8	73	69	67	64	73	69	66	64	72	68	66	64	71	68	66	64	63
	否	0.56	1.0	76	73	70	68	76	72	70	68	74	71	69	68	73	71	69	67	66
下方投影面積	等価発光面積	cm ²	1.25	79	76	73	71	78	75	73	71	77	74	72	71	75	73	72	70	69
			1.5	80	77	75	74	79	77	75	73	78	76	74	73	77	75	74	72	71
取付高さ	器具間隔最大限		2.0	82	80	78	77	81	79	78	76	80	78	77	76	78	77	76	75	74
	横方向 (A)	縦方向 (B)	2.5	83	81	80	79	82	81	79	78	81	80	78	77	79	78	77	77	75
H _m	0.41H _m	0.41H _m	3.0	84	82	81	80	83	82	81	80	82	80	79	79	80	79	78	78	76
			4.0	85	84	83	82	84	83	82	81	82	82	81	80	81	80	80	79	77
			5.0	86	85	84	83	85	84	83	82	83	82	82	81	81	81	80	80	78
			7.0	86	86	85	84	85	85	84	84	84	83	83	82	82	82	81	81	79
			10.0	87	86	86	85	86	85	85	85	84	84	83	83	82	82	82	82	80

