

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 2 5 K														
光源	LED5000_70_382 ×1					382.0 l m									
管理番号	K0146953 ( 0 ) DB 1														
B Z 分類	B Z 6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	33 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	67 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X0.01 )															Z C M		
保守率	良 中 否 0.63 0.6 0.56	0.6	49	37	29	23	46	35	27	22	40	31	25	20	35	28	22	19	14	
		0.8	58	46	38	32	54	44	36	31	48	39	33	28	42	35	29	25	20	
		1.0	64	53	45	39	60	50	43	37	53	45	38	34	46	40	34	30	24	
		1.25	70	59	51	45	66	56	49	43	58	50	44	39	50	44	40	36	29	
下方投影面積	c m <sup>2</sup>	1.5	74	64	56	50	69	61	54	48	61	54	49	44	54	48	43	40	32	
		2.0	79	71	64	58	75	67	61	56	66	60	55	51	58	53	49	46	37	
取付高さ	器具間隔最大限		2.5	83	75	69	64	78	72	66	61	69	64	59	55	61	57	53	50	41
	横方向 ( A )	縦方向 ( B )	3.0	85	79	73	68	81	75	70	65	72	67	63	59	63	59	56	53	44
H m	1.39 H m	1.39 H m	4.0	89	83	78	74	84	79	75	71	75	71	67	64	66	63	60	58	47
			5.0	91	86	82	78	86	82	78	75	77	73	70	68	68	65	63	61	50
			7.0	93	90	86	83	88	85	82	79	79	77	74	72	70	68	66	65	54
			10.0	95	93	90	88	90	88	86	83	81	79	77	76	72	71	69	68	56

