

屋内照明器具特性

品番 (品名) **LGB15493**

光源 **LLD5020LCC1 ×1** **1085.0 lm**

管理番号 **K0190424(0)DR1**

BZ分類 **BZ1**

器具効率	82%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	82%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	68	63	60	58	68	63	60	58	67	63	60	58	66	62	60	58	57	
	中 0.63	0.8	74	69	66	64	73	69	66	64	72	68	66	64	71	68	65	64	63	
	否 0.56	1.0	77	73	70	68	76	73	70	68	75	72	70	68	74	71	69	68	67	
下方投影面積	cm ²	1.25	79	76	74	72	79	76	73	72	77	75	73	71	76	74	72	71	70	
		1.5	81	78	76	74	80	78	76	74	79	77	75	74	78	76	74	73	72	
等価発光面積	cm ²	2.0	83	81	79	78	82	80	79	77	81	79	78	77	80	78	77	76	75	
		2.5	84	83	81	80	84	82	81	80	82	81	80	79	81	80	79	78	76	
取付高さ	器具間隔最大限		3.0	85	84	83	82	84	83	82	81	83	82	81	80	81	81	80	79	78
	横方向 (A)	縦方向 (B)	4.0	86	85	84	84	85	85	84	83	84	83	82	82	82	82	81	81	79
Hm	0.42Hm	0.42Hm	5.0	87	86	85	85	86	85	85	84	84	84	83	83	83	83	82	82	80
			7.0	88	87	87	86	87	86	86	86	85	85	85	84	84	83	83	83	81
			10.0	88	88	88	88	87	87	87	87	86	85	85	85	84	84	84	84	82

