

# 屋内照明器具特性

品番 (品名) **LGB16187**

光源 **LLD5020LCC1 ×1**      **1085.0 l m**

管理番号 **K0190421 (0) DR1**

BZ分類 **BZ1**

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	83 %		壁	10 %				10 %				10 %				10 %				
		床	10 %				10 %				10 %				10 %					
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	69	64	61	58	68	64	61	58	67	63	60	58	66	63	60	58	57
	中	0.63	0.8	75	70	67	65	74	70	67	65	73	69	66	65	71	68	66	64	63
	否	0.56	1.0	78	74	71	69	77	74	71	69	76	73	70	69	75	72	70	68	67
下方投影面積 等価発光面積	c m <sup>2</sup>	c m <sup>2</sup>	1.25	81	77	75	73	80	77	74	73	78	76	74	72	77	75	73	72	71
			1.5	82	79	77	75	82	79	77	75	80	78	76	75	79	77	75	74	73
			2.0	84	82	80	79	84	82	80	79	82	80	79	78	81	79	78	77	76
取付高さ	器具間隔最大限		2.5	86	84	82	81	85	83	82	81	83	82	81	80	82	81	80	79	77
	横方向 (A)	縦方向 (B)	3.0	87	85	84	83	86	84	83	82	84	83	82	81	83	82	81	80	79
H m	0.42 H m	0.42 H m	4.0	88	87	86	85	87	86	85	84	85	84	84	83	84	83	83	82	80
			5.0	88	88	87	86	87	87	86	86	86	85	85	84	84	84	83	83	81
			7.0	89	89	88	88	88	88	87	87	86	86	86	86	85	85	84	84	82
			10.0	90	89	89	89	89	88	88	87	87	87	87	85	85	85	85	83	

