

屋内照明器具特性

品番 (品名)	LGB16189															
光源	LLD5000LCC1 ×1 1140.0 1 m															
管理番号	K0190419 (0) DR 1															
BZ分類	BZ3 / 0.9 / BZ2															

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	94 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	61	51	45	41	60	51	45	41	58	50	44	40	56	49	44	40	39		
		0.8	71	62	56	52	70	62	56	52	68	61	55	52	66	60	55	51	50		
		1.0	77	69	64	60	76	69	64	60	74	68	63	59	72	66	62	59	57		
		1.25	82	76	71	67	81	75	70	67	79	74	69	66	77	72	69	66	64		
下方投影面積	c m ²	1.5	86	80	75	72	85	79	75	71	82	78	74	71	80	76	73	70	68		
		2.0	90	85	81	78	89	84	81	78	86	83	80	77	84	81	79	76	74		
取付高さ	器具間隔最大限		2.5	93	89	85	82	91	88	85	82	89	86	83	81	87	84	82	80	78	
	横方向 (A)	縦方向 (B)	3.0	94	91	88	85	93	90	87	85	91	88	86	84	89	86	84	83	80	
H m	1.27 H m	1.27 H m	4.0	96	94	91	89	95	93	90	89	93	91	89	87	91	89	87	86	84	
			5.0	97	95	93	92	96	94	93	91	94	92	91	89	92	91	89	88	86	
			7.0	99	97	96	94	98	96	95	94	95	94	93	92	93	92	91	91	88	
			10.0	100	99	98	97	99	98	97	96	96	95	94	94	94	93	92	90		

