

# 屋内照明器具特性

品番 (品名) **LGB16189**

光源 **LLD5010LCC1 x1** **1095.0 1m**

管理番号 **K0190420(0)DR1**

BZ分類 **BZ1**

器具効率	96%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	96%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	82	76	72	70	81	76	72	70	80	75	72	70	79	75	72	70	69
	中	0.63	0.8	87	82	79	76	86	82	78	76	85	81	78	76	84	80	77	75	74
	否	0.56	1.0	90	86	83	80	90	85	82	80	88	84	82	80	87	84	81	79	78
下方投影面積	cm <sup>2</sup>	1.25	93	89	86	84	92	89	86	84	91	88	85	83	89	87	85	83	82	
		1.5	95	92	89	87	94	91	88	86	92	90	88	86	91	89	87	85	84	
等価発光面積	cm <sup>2</sup>	2.0	97	95	92	90	96	94	92	90	95	92	91	89	93	91	90	88	87	
		2.5	99	96	94	93	98	96	94	92	96	94	93	91	94	93	91	90	88	
取付高さ	器具間隔最大限		3.0	100	98	96	94	99	97	95	94	97	95	94	93	95	94	93	92	90
	横方向 (A)	縦方向 (B)	4.0	101	99	98	97	100	98	97	96	98	97	96	95	96	95	94	93	91
Hm	0.83Hm	0.83Hm	5.0	102	100	99	98	101	99	98	97	99	98	97	96	97	96	95	94	92
			7.0	102	101	101	100	101	100	99	99	99	98	97	97	97	96	96	96	93
			10.0	103	102	102	101	102	101	101	100	100	99	99	98	98	97	97	94	

