

屋内照明器具特性

| | | |
|---------|---------------------|----------|
| 品番 (品名) | XLGB1063 | |
| 光源 | LLD2000VCE1 ×1 | 531.0 lm |
| 管理番号 | K0190090(1)DR1 | |
| BZ分類 | BZ3/0.7/BZ2/1.8/BZ3 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率 | 70% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 1% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 69% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | 照明率 (×0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 45 | 38 | 34 | 30 | 45 | 38 | 33 | 30 | 43 | 37 | 33 | 30 | 42 | 36 | 33 | 30 | 29 |
| | 中 | 0.63 | 0.8 | 52 | 46 | 41 | 38 | 51 | 45 | 41 | 38 | 50 | 45 | 41 | 38 | 48 | 44 | 40 | 38 | 37 |
| | 否 | 0.56 | 1.0 | 57 | 51 | 47 | 44 | 56 | 50 | 46 | 43 | 54 | 49 | 46 | 43 | 52 | 48 | 45 | 43 | 41 |
| | | | 1.25 | 60 | 55 | 51 | 48 | 59 | 54 | 51 | 48 | 57 | 53 | 50 | 48 | 56 | 52 | 50 | 47 | 46 |
| 下方投影面積 | cm ² | | 1.5 | 63 | 58 | 54 | 51 | 62 | 57 | 54 | 51 | 60 | 56 | 53 | 51 | 58 | 55 | 52 | 50 | 49 |
| 等価発光面積 | cm ² | | 2.0 | 66 | 62 | 59 | 56 | 65 | 61 | 58 | 56 | 63 | 60 | 57 | 55 | 61 | 59 | 56 | 55 | 53 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 68 | 64 | 62 | 59 | 67 | 64 | 61 | 59 | 65 | 62 | 60 | 58 | 63 | 61 | 59 | 57 | 56 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 69 | 66 | 64 | 62 | 68 | 65 | 63 | 61 | 66 | 64 | 62 | 60 | 64 | 62 | 61 | 59 | 58 |
| Hm | 1.31Hm | 1.31Hm | 4.0 | 70 | 68 | 66 | 65 | 69 | 67 | 66 | 64 | 68 | 66 | 64 | 63 | 66 | 65 | 63 | 62 | 60 |
| | | | 5.0 | 71 | 70 | 68 | 66 | 70 | 69 | 67 | 66 | 69 | 67 | 66 | 65 | 67 | 66 | 65 | 64 | 62 |
| | | | 7.0 | 72 | 71 | 70 | 69 | 72 | 70 | 69 | 68 | 70 | 69 | 68 | 67 | 68 | 67 | 66 | 66 | 64 |
| | | | 10.0 | 73 | 72 | 71 | 71 | 72 | 72 | 71 | 70 | 71 | 70 | 69 | 69 | 69 | 68 | 68 | 67 | 65 |

