

屋内照明器具特性

品番 (品名)	XLGB1069				
光源	LLD2000VCE1 ×1 531.0 lm				
管理番号	K0190090 (1) DR1				
BZ分類	BZ3/0.7/BZ2/1.8/BZ3				

器具効率	70%	天井	80%				70%				50%				30%				0%				
	上方光束 1%		下方光束 69%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				室指数	照明率 (X0.01) ZCM																		
保守率	良 0.67	中 否 0.63 0.56	0.6	45	38	34	30	45	38	33	30	43	37	33	30	42	36	33	30	29			
	1.0		57	51	47	44	56	50	46	43	54	49	46	43	52	48	45	43	41				
	1.25		60	55	51	48	59	54	51	48	57	53	50	48	56	52	50	47	46				
	1.5		63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49				
下方投影面積 等価発光面積	cm ²		2.0	66	62	59	56	65	61	58	56	63	60	57	55	61	59	56	55	53			
	cm ²		2.5	68	64	62	59	67	64	61	59	65	62	60	58	63	61	59	57	56			
取付高さ	器具間隔最大限		Hm	1.31Hm	1.31Hm	3.0	69	66	64	62	68	65	63	61	66	64	62	60	64	62	61	59	58
	Hm					4.0	70	68	66	65	69	67	66	64	68	66	64	63	66	65	63	62	60
			5.0	71	70	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62			
			7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64			
			10.0	73	72	71	71	72	72	71	70	71	70	69	69	69	68	68	67	65			

