

屋内照明器具特性	
品番(品名)	S L B 1 9 4 6 1 W
光源	LDA7L-D-G/S/Z6 ×4 810.0 lm
管理番号	K0140282(0)DB1
BZ分類	BZ8

器具効率	90%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	39%	反射率	10%				10%				10%				10%				0%	
下方光束	51%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	41	29	22	17	38	27	21	16	31	23	18	14	26	19	15	12	7
	中	0.6	0.8	48	37	29	24	44	34	27	22	37	29	24	19	31	25	20	16	11
	否	0.56	1.0	54	43	35	29	49	40	33	27	41	34	28	24	34	28	24	20	13
			1.25	59	48	41	35	54	45	38	33	45	38	33	28	38	32	28	24	16
下方投影面積		cm ²	1.5	62	53	45	39	57	49	42	37	48	42	36	32	40	35	31	27	19
等価発光面積		cm ²	2.0	67	59	52	47	62	55	49	44	53	47	42	38	44	39	36	32	23
取付高さ	器具間隔最大限		2.5	71	63	57	52	65	59	53	48	56	51	46	42	47	43	39	36	26
	横方向(A)	縦方向(B)	3.0	73	66	61	56	68	62	57	52	58	53	49	45	49	45	42	39	28
Hm	1.43Hm	1.43Hm	4.0	76	71	66	61	71	66	62	58	61	57	53	50	51	48	46	43	32
			5.0	78	73	69	65	73	69	65	61	63	59	56	53	53	51	48	46	34
			7.0	81	77	74	70	75	72	69	66	65	63	60	58	56	53	51	50	37
			10.0	83	80	77	75	77	75	72	70	67	65	63	61	58	56	54	53	40

