

屋内照明器具特性	
品番 (品名)	NYM20256+NYK00117
光源	LED5000_85_47880 ×1 47880.0 lm
管理番号	K0185714 (0) DB1
BZ分類	BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	6 5	5 5	4 8	4 4	6 4	5 4	4 8	4 4	6 2	5 3	4 8	4 4	6 0	5 2	4 7	4 3	4 1	
			0 . 8	7 5	6 5	5 9	5 4	7 3	6 5	5 9	5 4	7 1	6 3	5 8	5 4	6 8	6 2	5 7	5 3	5 1	
			1 . 0	8 1	7 2	6 6	6 2	7 9	7 1	6 6	6 1	7 7	7 0	6 5	6 1	7 4	6 8	6 4	6 0	5 8	
			0 . 7 7	1 . 2 5	8 6	7 8	7 3	6 8	8 4	7 7	7 2	6 8	8 1	7 6	7 1	6 7	7 9	7 4	7 0	6 6	6 4
下方投影面積 等価発光面積		c m ²	1 . 5	8 9	8 2	7 7	7 3	8 8	8 1	7 7	7 3	8 5	7 9	7 5	7 2	8 2	7 8	7 4	7 1	6 8	
			2 . 0	9 4	8 8	8 4	8 0	9 2	8 7	8 3	7 9	8 9	8 5	8 1	7 8	8 6	8 3	8 0	7 7	7 4	
			2 . 5	9 6	9 2	8 8	8 4	9 5	9 1	8 7	8 4	9 2	8 8	8 5	8 2	8 9	8 6	8 3	8 1	7 8	
取付 高さ	器具間隔最大限		3 . 0	9 8	9 4	9 1	8 8	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 1	8 8	8 6	8 4	8 1	
	横方向 (A)	縦方向 (B)	4 . 0	1 0 1	9 7	9 5	9 2	9 9	9 6	9 3	9 1	9 6	9 4	9 1	8 9	9 3	9 1	8 9	8 8	8 5	
H m	1 . 2 4 H m	1 . 2 4 H m	5 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 5	9 3	9 2	9 0	8 7	
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	9 9	9 8	9 6	9 5	9 7	9 5	9 4	9 3	9 0	
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2	

