

屋内照明器具特性

品番 (品名)	NYM20263+NYK00118	
光源	LED5000_85_21750 ×1	21750.0 1 m
管理番号	K0185728 (0) DB 1	
BZ分類	BZ3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	6 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.77	0.6	65	55	48	44	64	54	48	44	61	53	47	43	59	51	46	43	41
		0.72	0.8	74	65	58	54	72	64	58	53	69	62	57	53	67	60	56	52	50
			1.0	80	71	65	60	78	70	64	60	75	68	63	59	72	66	62	58	56
		0.68	1.25	85	77	71	67	83	76	70	66	79	73	69	65	76	71	67	64	61
下方投影面積	c m ²	1.5	88	81	76	71	86	80	75	71	83	77	73	69	79	75	71	68	65	
		2.0	92	87	82	78	90	85	81	77	87	82	79	76	83	80	77	74	71	
取付高さ	器具間隔最大限		2.5	95	90	86	82	93	89	85	81	90	86	83	80	86	83	80	78	74
	横方向 (A)	縦方向 (B)	3.0	97	93	89	86	95	91	88	85	91	88	85	83	88	85	83	81	77
H m	1.11H m	1.11H m	4.0	99	96	93	90	97	94	92	89	94	91	89	87	90	88	86	85	81
			5.0	101	98	95	93	99	96	94	92	95	93	91	89	92	90	88	87	83
			7.0	103	100	98	97	101	99	97	95	97	95	94	93	94	92	91	90	86
			10.0	104	102	101	99	102	101	99	98	98	97	96	95	95	94	93	92	88

