

屋内照明器具特性

品番 (品名)	XAD3 1 1 2 L K				
光源	LLD4000MLCB1 ×1		845.0 l m		
管理番号	K0175542 (0) DR 1				
B Z 分類	B Z 3				

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																Z C M		
下方光束	64 %																				
保守率	良 中 否	0.67	0.6	41	35	30	27	40	34	30	27	39	34	30	27	38	33	30	27	26	
		0.63	0.8	47	41	37	34	47	41	37	34	45	40	37	34	44	39	36	34	33	
			1.0	51	46	42	39	50	45	42	39	49	44	41	38	47	44	41	38	37	
		0.56	1.25	55	50	46	43	54	49	46	43	52	48	45	43	51	47	45	42	41	
下方投影面積	c m ²	1.5	57	52	49	46	56	52	49	46	54	51	48	46	53	50	47	45	44		
		2.0	60	56	53	51	59	55	53	50	57	54	52	50	56	53	51	49	48		
取付高さ	器具間隔最大限		2.5	62	58	56	53	61	58	55	53	59	56	54	53	57	55	53	52	50	
	横方向 (A)	縦方向 (B)	3.0	63	60	58	56	62	59	57	55	60	58	56	54	59	57	55	54	52	
H m	1.18 H m	1.18 H m	4.0	64	62	60	58	63	61	60	58	62	60	59	57	60	59	57	56	55	
			5.0	65	63	62	60	64	63	61	60	63	61	60	59	61	60	59	58	56	
			7.0	66	65	64	62	65	64	63	62	64	63	62	61	62	61	61	60	58	
			10.0	67	66	65	64	66	65	64	64	65	64	63	62	63	63	62	61	59	

