

| 屋内照明器具特性 | |
|----------|----------------------------|
| 品番(品名) | LGW80300K(WALL) |
| 光源 | LED2700_70_289 x1 289.0 lm |
| 管理番号 | K0149618(0)DR1 |
| BZ分類 | BZ10/0.9/BZ9 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 50% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 50% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.63 | 0.6 | 43 | 31 | 22 | 17 | 39 | 28 | 21 | 15 | 32 | 23 | 17 | 13 | 25 | 18 | 13 | 10 | 4 |
| | 中 | 0.6 | 0.8 | 52 | 39 | 30 | 24 | 47 | 36 | 28 | 22 | 38 | 29 | 23 | 18 | 30 | 23 | 18 | 14 | 8 |
| | 否 | 0.56 | 1.0 | 58 | 45 | 37 | 30 | 52 | 41 | 34 | 28 | 43 | 34 | 28 | 23 | 34 | 27 | 22 | 18 | 10 |
| | | | 1.25 | 63 | 52 | 43 | 36 | 57 | 47 | 39 | 33 | 47 | 39 | 33 | 28 | 37 | 31 | 26 | 22 | 13 |
| 下方投影面積 | | cm ² | 1.5 | 67 | 56 | 48 | 41 | 61 | 52 | 44 | 38 | 50 | 43 | 37 | 32 | 40 | 34 | 30 | 26 | 16 |
| 等価発光面積 | | cm ² | 2.0 | 73 | 63 | 56 | 49 | 67 | 58 | 51 | 46 | 55 | 48 | 43 | 38 | 44 | 39 | 35 | 31 | 20 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 77 | 68 | 61 | 55 | 70 | 63 | 56 | 51 | 58 | 52 | 47 | 43 | 47 | 43 | 39 | 35 | 23 |
| | 横方向(A) | 縦方向(B) | 3.0 | 79 | 72 | 65 | 60 | 73 | 66 | 60 | 55 | 61 | 55 | 51 | 47 | 49 | 45 | 42 | 38 | 25 |
| Hm | 0.00Hm | 1.54Hm | 4.0 | 83 | 77 | 71 | 66 | 76 | 71 | 66 | 61 | 64 | 60 | 56 | 52 | 52 | 49 | 46 | 43 | 29 |
| | | | 5.0 | 85 | 80 | 75 | 70 | 79 | 74 | 69 | 65 | 66 | 62 | 59 | 56 | 54 | 51 | 49 | 46 | 31 |
| | | | 7.0 | 88 | 84 | 80 | 76 | 82 | 78 | 74 | 71 | 69 | 66 | 63 | 60 | 57 | 55 | 52 | 50 | 35 |
| | | | 10.0 | 90 | 87 | 84 | 81 | 84 | 81 | 78 | 75 | 71 | 69 | 67 | 64 | 59 | 57 | 56 | 54 | 38 |

