

屋内照明器具特性	
品番 (品名)	NY Y5 6 0 4 9 K+ N T S 9 0 0 6 0
光源	LED4000_85_535 ×1 535.0 lm
管理番号	K0149446 (0) DB 1
B Z 分類	B Z 1

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
						室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 8 1	0 . 6	7 5	6 7	6 2	5 8	7 4	6 7	6 2	5 8	7 2	6 6	6 1	5 8	7 1	6 5	6 1	5 8	5 7					
			0 . 7 7	0 . 8	8 3	7 6	7 1	6 7	8 2	7 5	7 1	6 7	8 0	7 4	7 0	6 7	7 8	7 3	7 0	6 7	6 5					
			0 . 6 8	1 . 0	8 8	8 1	7 7	7 3	8 7	8 1	7 7	7 3	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 2	7 1					
			1 . 2 5	9 2	8 6	8 2	7 9	9 1	8 6	8 2	7 9	8 9	8 4	8 1	7 8	8 7	8 3	8 0	7 8	7 6						
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	9 5	9 0	8 6	8 3	9 4	8 9	8 5	8 2	9 1	8 7	8 4	8 2	8 9	8 6	8 3	8 1	7 9						
			2 . 0	9 8	9 4	9 1	8 8	9 7	9 3	9 0	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4						
			2 . 5	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 7						
取付 高さ	器具間隔最大限		3 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 9						
	横方向 (A)	縦方向 (B)	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1						
H m	1 . 1 9 H m	1 . 1 9 H m	5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 6	9 5	9 3						
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5						
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6						

