

屋内照明器具特性	
品番 (品名)	NYM20246+NYK00119
光源	LED5000_85_43840 ×1 43840.0 lm
管理番号	K0185708(0)DB1
BZ分類	BZ1/0.7/BZ2/3.5/BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.77	0.6	71	62	56	52	70	61	56	52	67	60	55	52	65	59	55	51	50
	中	0.72	0.8	78	70	65	61	77	69	64	60	74	68	63	60	72	66	62	59	57
	否	0.68	1.0	83	76	70	66	82	75	70	66	79	73	69	65	77	71	68	65	62
			1.25	88	81	76	72	86	80	75	71	83	78	74	70	80	76	72	69	67
下方投影面積	c m ²		1.5	91	84	80	76	89	83	79	75	86	81	77	74	83	79	76	73	70
	等価発光面積		c m ²	2.0	95	89	85	82	93	88	84	81	90	86	82	79	87	83	80	78
取付高さ	器具間隔最大限		2.5	97	92	89	86	95	91	88	85	92	89	86	83	89	86	84	81	78
	横方向 (A)	縦方向 (B)	3.0	99	95	91	88	97	93	90	87	94	91	88	86	90	88	86	84	81
H m	0.87 H m	0.87 H m	4.0	101	98	95	92	99	96	94	91	96	93	91	89	93	91	89	87	84
			5.0	102	99	97	95	100	98	96	94	97	95	93	92	94	92	91	89	86
			7.0	104	102	100	98	102	100	98	97	99	97	96	94	95	94	93	92	88
			10.0	105	103	102	101	103	102	100	99	100	99	98	97	97	96	95	94	90

