

屋内照明器具特性

品番 (品名)	L G W 8 0 3 3 2 K	
光源	LED5000_70_174 ×1	174.0 l m
管理番号	K0146949 (0) DB 1	
B Z 分類	B Z 6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 22 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	78 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																				Z C M
保守率	良	0.63	0.6	51	39	31	26	49	38	30	25	44	35	28	24	40	32	27	22	19	
	中	0.6	0.8	61	49	41	35	58	47	39	34	52	43	37	32	48	40	34	30	26	
	否	0.56	1.0	67	55	47	41	64	53	46	40	58	49	43	38	52	45	40	36	31	
			1.25	72	62	54	48	69	59	52	46	63	55	49	44	57	51	45	41	36	
下方投影面積	c m ²		1.5	76	67	59	53	73	64	57	51	66	59	53	48	60	54	49	45	40	
等価発光面積	c m ²		2.0	82	73	66	60	78	70	64	59	71	65	60	55	65	60	55	51	45	
取付高さ	器具間隔最大限		2.5	85	77	71	66	81	74	69	64	74	69	64	60	68	63	59	56	49	
	横方向 (A)	縦方向 (B)	3.0	87	81	75	70	84	78	72	68	77	72	67	63	70	66	62	59	52	
H m	1.25 H m	1.25 H m	4.0	91	85	80	76	87	82	77	73	80	76	72	68	73	70	67	64	56	
			5.0	93	88	84	80	89	85	81	77	82	78	75	72	75	72	70	67	59	
			7.0	95	92	88	85	92	88	85	82	85	82	79	76	78	75	73	71	63	
			10.0	97	95	92	89	94	91	89	86	87	85	82	81	80	78	77	75	66	

