

屋内照明器具特性

品番 (品名)	XLGB1731																
光源	LLD4000VCE1 ×1 845.0 lm																
管理番号	K0185491 (0) DR1																
BZ分類	BZ4/0.7/BZ3																

器具効率	79%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01) ZCM																	
下方光束	79%																			
保守率	良 中 否	0.67	0.6	48	39	33	29	47	39	33	29	45	38	33	29	44	37	33	29	28
		0.63	0.8	57	49	43	39	56	48	43	39	54	47	43	39	52	46	42	39	37
			1.0	63	55	50	46	62	55	50	46	60	54	49	46	58	53	49	46	44
		0.56	1.25	67	61	56	53	66	60	56	52	64	59	55	52	62	58	55	52	50
下方投影面積	c m ²	1.5	70	65	60	57	69	64	60	57	67	63	59	56	65	61	58	56	54	
		2.0	74	70	66	63	73	69	66	63	71	68	65	62	69	66	64	61	60	
取付高さ	器具間隔最大限		2.5	77	73	70	67	76	72	69	66	73	71	68	66	72	69	67	65	63
	横方向 (A)	縦方向 (B)	3.0	78	75	72	70	77	74	71	69	75	73	70	68	73	71	69	67	66
H m	1.28 H m	1.28 H m	4.0	80	78	75	73	79	77	75	73	77	75	73	72	75	74	72	71	69
			5.0	81	79	77	76	80	78	77	75	78	77	75	74	76	75	74	73	71
			7.0	83	81	80	78	82	80	79	78	80	78	77	76	78	77	76	75	73
			10.0	84	82	81	80	83	82	81	80	81	80	79	78	79	78	77	75	73

