

屋内照明器具特性	
品番 (品名)	SLB81307+SLK29002
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0195408(0)DR1
BZ分類	BZ7

器具効率	81%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	41%	床	10%				10%				10%				10%				0%	
下方光束	40%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	3.7	2.8	2.2	1.7	3.4	2.6	2.0	1.6	2.8	2.2	1.7	1.4	2.3	1.8	1.4	1.2	7	
	中 0.6	0.8	4.4	3.5	2.8	2.3	4.0	3.2	2.6	2.2	3.4	2.7	2.2	1.9	2.7	2.2	1.8	1.6	10	
	否 0.56	1.0	4.9	4.0	3.3	2.8	4.5	3.7	3.1	2.6	3.7	3.1	2.6	2.2	3.0	2.5	2.2	1.9	12	
		1.25	5.3	4.5	3.8	3.3	4.9	4.1	3.5	3.1	4.0	3.5	3.0	2.6	3.3	2.8	2.5	2.2	15	
下方投影面積	cm ²	1.5	5.6	4.8	4.2	3.7	5.2	4.5	3.9	3.5	4.3	3.8	3.3	3.0	3.5	3.1	2.8	2.5	17	
等価発光面積		2.0	6.1	5.4	4.8	4.3	5.6	5.0	4.5	4.0	4.7	4.2	3.8	3.5	3.8	3.5	3.1	2.9	20	
取付高さ		器具間隔最大限		2.5	6.4	5.7	5.2	4.8	5.8	5.3	4.9	4.5	4.9	4.5	4.1	3.8	4.0	3.7	3.4	2.2
Hm		横方向(A)	縦方向(B)	3.0	6.6	6.0	5.5	5.1	6.0	5.6	5.1	4.8	5.1	4.7	4.4	4.1	4.2	3.9	3.6	2.4
	1.13Hm	1.13Hm	4.0	6.8	6.4	6.0	5.6	6.3	5.9	5.5	5.2	5.3	5.0	4.7	4.5	4.4	4.2	3.9	2.6	
			5.0	7.0	6.6	6.3	5.9	6.5	6.1	5.8	5.5	5.5	5.2	5.0	4.7	4.5	4.3	4.1	2.8	
			7.0	7.2	6.9	6.6	6.4	6.7	6.4	6.2	5.9	5.7	5.5	5.3	5.1	4.7	4.6	4.4	3.0	
			10.0	7.4	7.1	6.9	6.7	6.8	6.6	6.4	6.3	5.8	5.7	5.5	5.4	4.9	4.7	4.6	3.2	

