

屋内照明器具特性	
品番 (品名)	SLB81307+SLK29002
光源	LLD3411VCB1 ×1                      700.0 1 m
管理番号	K0195409 ( 0 ) DR 1
B Z 分類	BZ6

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		44 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		44 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	4.2	3.2	2.6	2.1	3.9	3.0	2.4	2.0	3.3	2.6	2.1	1.7	2.7	2.1	1.8	1.5	1.0	
	中	0.6	0.8	4.9	3.9	3.3	2.8	4.5	3.7	3.0	2.6	3.8	3.1	2.6	2.3	3.1	2.6	2.2	1.9	1.3	
	否	0.56	1.0	5.4	4.5	3.8	3.3	5.0	4.2	3.5	3.1	4.2	3.5	3.0	2.7	3.4	2.9	2.6	2.3	1.6	
			1.25	5.9	5.0	4.3	3.8	5.4	4.6	4.0	3.6	4.5	3.9	3.5	3.1	3.7	3.3	2.9	2.6	1.8	
下方投影面積	c m <sup>2</sup>		1.5	6.2	5.4	4.8	4.3	5.7	5.0	4.4	4.0	4.8	4.2	3.8	3.4	3.9	3.5	3.2	2.9	2.0	
等価発光面積	c m <sup>2</sup>		2.0	6.7	6.0	5.4	4.9	6.2	5.5	5.0	4.6	5.2	4.7	4.3	4.0	4.3	3.9	3.6	3.3	2.3	
取付高さ	器具間隔最大限		2.5	7.0	6.4	5.8	5.4	6.5	5.9	5.4	5.0	5.4	5.0	4.6	4.3	4.5	4.2	3.9	3.6	2.6	
	横方向 (A)	縦方向 (B)	3.0	7.2	6.6	6.2	5.7	6.7	6.2	5.7	5.4	5.6	5.2	4.9	4.6	4.6	4.4	4.1	3.9	2.8	
H m	0.62 H m	0.62 H m	4.0	7.5	7.0	6.6	6.3	6.9	6.5	6.2	5.8	5.9	5.6	5.3	5.0	4.9	4.6	4.4	4.2	3.0	
			5.0	7.7	7.3	6.9	6.6	7.1	6.8	6.4	6.1	6.0	5.8	5.5	5.3	5.0	4.8	4.6	4.4	3.2	
			7.0	7.9	7.6	7.3	7.0	7.3	7.0	6.8	6.6	6.2	6.0	5.8	5.6	5.2	5.0	4.9	4.7	3.4	
			10.0	8.0	7.8	7.6	7.4	7.5	7.3	7.1	6.9	6.4	6.2	6.1	5.9	5.3	5.2	5.1	5.0	3.6	

