

屋内照明器具特性	
品番 (品名)	LGB16459K
光源	LDA4 WW- H- E17 / S / 4 ×1 440.0 1 m
管理番号	K0164281 (1) DB 1
BZ分類	BZ4 / 0.7 / BZ3 / 1.8 / BZ4

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	52 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	3.4	2.7	2.3	2.0	3.3	2.7	2.3	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	1.9	1.8			
	中	0.63	0.8	3.9	3.4	3.0	2.7	3.8	3.3	2.9	2.6	3.6	3.2	2.8	2.6	3.4	3.0	2.8	2.5	2.4			
	否	0.56	1.0	4.3	3.8	3.4	3.1	4.2	3.7	3.3	3.1	4.0	3.6	3.2	3.0	3.8	3.4	3.1	2.9	2.8			
			1.25	4.6	4.1	3.8	3.5	4.5	4.1	3.7	3.5	4.3	3.9	3.6	3.4	4.1	3.7	3.5	3.3	3.1			
下方投影面積	c m <sup>2</sup>	1.5	4.8	4.4	4.1	3.8	4.7	4.3	4.0	3.7	4.5	4.1	3.9	3.7	4.2	4.0	3.7	3.6	3.4				
		2.0	5.1	4.8	4.5	4.2	5.0	4.7	4.4	4.2	4.7	4.5	4.2	4.0	4.5	4.3	4.1	3.9	3.7				
取付高さ	器具間隔最大限		2.5	5.3	5.0	4.7	4.5	5.2	4.9	4.6	4.4	4.9	4.7	4.5	4.3	4.7	4.5	4.3	4.2	3.9			
	横方向 (A)	縦方向 (B)	3.0	5.4	5.1	4.9	4.7	5.3	5.0	4.8	4.6	5.0	4.8	4.6	4.5	4.8	4.6	4.5	4.3	4.1			
H m	1.37 H m	1.40 H m	4.0	5.6	5.3	5.1	5.0	5.4	5.2	5.1	4.9	5.2	5.0	4.9	4.7	4.9	4.8	4.7	4.6	4.3			
			5.0	5.6	5.5	5.3	5.2	5.5	5.3	5.2	5.1	5.3	5.1	5.0	4.9	5.0	4.9	4.8	4.7	4.4			
			7.0	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.3	5.2	5.1	5.1	5.1	5.0	4.9	4.6			
			10.0	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.5	5.4	5.3	5.2	5.2	5.2	5.1	5.0	4.7			

