

屋内照明器具特性

品番 (品名)	LGB16446K														
光源	LDA4L-H-E17/S/4 ×1 440.0lm														
管理番号	K0185437(0)DR1														
BZ分類	BZ5														

器具効率	93%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	14% 79%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	49	38	31	25	47	37	30	25	44	35	28	24	40	33	27	23	20		
		0.8	59	48	40	35	56	46	40	34	52	44	38	33	48	41	36	32	29		
		1.0	65	55	48	42	62	53	47	41	58	50	44	40	54	47	42	38	35		
		1.25	71	61	55	49	68	60	53	48	63	56	51	46	59	53	48	44	40		
下方投影面積 等価発光面積	c m ² c m ²	1.5	74	66	60	54	72	64	58	53	67	60	55	51	62	57	52	49	44		
		2.0	80	73	67	62	77	70	65	61	72	66	62	58	67	62	59	56	51		
取付 高さ	器具間隔最大限		2.5	83	77	72	67	80	75	70	66	75	70	66	63	70	66	63	60	55	
	横方向 (A) H m	縦方向 (B) H m	3.0	85	80	75	71	82	77	73	70	77	73	69	66	72	69	66	63	58	
			4.0	88	84	80	77	85	81	78	75	80	77	74	71	75	72	70	68	62	
			5.0	90	86	83	80	87	84	81	78	82	79	76	74	77	74	72	71	65	
			7.0	92	89	87	84	89	87	84	82	84	82	80	78	79	77	76	74	68	
			10.0	93	91	90	88	91	89	87	85	85	84	82	81	80	79	78	77	70	

