

屋内照明器具特性

品番 (品名)	XAD3 4 4 0 L	
光源	LLD4000LCE1 ×1	845.0 l m
管理番号	K0175553 (0) DR 1	
B Z 分類	B Z 5	

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	83 %	室指数	照明率 (X0.01)																Z C M	
保守率	良	0.67	0.6	47	37	31	26	46	37	31	26	44	36	30	26	43	35	30	26	25
	中	0.63	0.8	56	46	40	35	54	46	40	35	52	45	39	35	50	43	38	35	33
	否	0.56	1.0	61	52	46	41	60	52	46	41	57	50	45	41	55	49	44	41	39
			1.25	66	58	52	48	65	57	52	47	62	56	51	47	60	55	50	47	45
下方投影面積		cm ²	1.5	70	62	57	52	68	62	56	52	66	60	55	52	63	58	54	51	49
等価発光面積		cm ²	2.0	74	68	63	59	73	67	63	59	70	66	62	58	68	64	61	58	56
取付高さ	器具間隔最大限		2.5	77	72	68	64	76	71	67	64	73	69	66	63	71	68	65	62	60
	横方向 (A)	縦方向 (B)	3.0	79	75	71	67	78	74	70	67	75	72	69	66	73	70	68	65	63
H m	1.25 H m	1.25 H m	4.0	82	78	75	72	80	77	74	72	78	75	73	71	76	74	72	70	67
			5.0	83	80	78	75	82	79	77	75	80	78	75	74	78	76	74	72	70
			7.0	85	83	81	79	84	82	80	78	82	80	79	77	80	78	77	76	73
			10.0	86	85	83	82	85	84	83	81	83	82	81	80	81	80	79	78	76

