

# 屋内照明器具特性

品番 (品名)	YYY46044Z									
光源	LED4000_70_4320 x1					4320.0 lm				
管理番号	K0147808(0)DB1									
BZ分類	BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 100%	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.69	0.6	64	53	46	42	63	53	46	42	61	52	46	41	59	51	45	41	40
	中	0.67	0.8	74	64	58	53	73	64	57	53	70	62	57	53	68	61	56	52	51
	否	0.63	1.0	80	72	65	61	79	71	65	61	77	70	64	60	74	68	64	60	58
			1.25	86	78	72	68	84	77	72	68	82	76	71	67	80	74	70	67	65
下方投影面積			1.5	89	83	77	73	88	82	77	73	85	80	76	72	83	78	75	72	69
	等価発光面積		2.0	94	89	84	80	93	88	83	80	90	86	82	79	88	84	81	78	76
取付高さ	器具間隔最大限		2.5	97	92	88	85	96	91	88	84	93	89	86	83	91	88	85	82	80
	横方向 (A)	縦方向 (B)	3.0	99	95	91	88	98	94	91	88	95	92	89	87	93	90	88	85	83
Hm	1.07Hm	1.15Hm	4.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	89	87
			5.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	92	89
			7.0	104	102	101	99	103	101	100	98	101	99	98	96	98	97	96	95	92
			10.0	105	104	103	102	104	103	102	101	102	101	100	99	99	99	98	97	94

