

屋内照明器具特性

品番 (品名)	XLGB1868	
光源	LLD2000LCE1 ×1	531.0 lm
管理番号	K0190090(1)DR1	
BZ分類	BZ3/0.7/BZ2/1.8/BZ3	

器具効率	70%	天井	80%				70%				50%				30%				0%																						
	上方光束 1%		下方光束 69%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																				
				壁	10%				10%				10%				10%				0%																				
床	室指数																				照明率 (×0.01)																				ZCM
保守率	良	0.67	0.6	45	38	34	30	45	38	33	30	43	37	33	30	42	36	33	30	29																					
	中	0.63	0.8	52	46	41	38	51	45	41	38	50	45	41	38	48	44	40	38	37																					
	否	0.56	1.0	57	51	47	44	56	50	46	43	54	49	46	43	52	48	45	43	41																					
			1.25	60	55	51	48	59	54	51	48	57	53	50	48	56	52	50	47	46																					
下方投影面積 等価発光面積	cm ²		1.5	63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49																					
	cm ²		2.0	66	62	59	56	65	61	58	56	63	60	57	55	61	59	56	55	53																					
	器具間隔最大限		2.5	68	64	62	59	67	64	61	59	65	62	60	58	63	61	59	57	56																					
取付高さ	Hm		3.0	69	66	64	62	68	65	63	61	66	64	62	60	64	62	61	59	58																					
	Hm		4.0	70	68	66	65	69	67	66	64	68	66	64	63	66	65	63	62	60																					
Hm	Hm		5.0	71	70	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62																					
	Hm		7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64																					
	Hm		10.0	73	72	71	71	72	72	71	70	71	70	69	69	69	68	68	67	65																					

