

屋内照明器具特性	
品番 (品名)	XFL323SC
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m
管理番号	K0126143(1)DB1
BZ分類	BZ3

器具効率	66%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	66%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	4.2	3.5	3.0	2.7	4.1	3.4	3.0	2.7	4.0	3.4	3.0	2.7	3.8	3.3	2.9	2.7	2.5			
	中	0.77	0.8	4.9	4.2	3.8	3.5	4.8	4.2	3.8	3.5	4.6	4.1	3.7	3.5	4.5	4.0	3.7	3.4	3.3			
	否	0.68	1.0	5.3	4.7	4.3	4.0	5.2	4.7	4.3	4.0	5.1	4.6	4.3	4.0	4.9	4.5	4.2	4.0	3.8			
			1.25	5.7	5.2	4.8	4.5	5.6	5.1	4.8	4.5	5.4	5.0	4.7	4.5	5.3	4.9	4.7	4.4	4.3			
下方投影面積		cm ²	1.5	5.9	5.5	5.1	4.9	5.8	5.4	5.1	4.8	5.7	5.3	5.0	4.8	5.5	5.2	5.0	4.8	4.6			
等価発光面積		cm ²	2.0	6.2	5.9	5.6	5.3	6.1	5.8	5.5	5.3	6.0	5.7	5.5	5.2	5.8	5.6	5.4	5.2	5.1			
取付高さ	器具間隔最大限		2.5	6.4	6.1	5.9	5.6	6.3	6.1	5.8	5.6	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.5	5.3			
	横方向 (A)	縦方向 (B)	3.0	6.5	6.3	6.1	5.9	6.5	6.2	6.0	5.8	6.3	6.1	5.9	5.7	6.1	6.0	5.8	5.7	5.5			
1.5m	2.33m	1.93m	4.0	6.7	6.5	6.3	6.2	6.6	6.4	6.3	6.1	6.5	6.3	6.2	6.0	6.3	6.2	6.0	5.9	5.8			
2	3.09	2.4	5.0	6.8	6.6	6.5	6.3	6.7	6.6	6.4	6.3	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	5.9			
2.5	3.85	2.88	7.0	6.9	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.1			
3	4.6	3.37	10.0	7.0	6.9	6.8	6.7	6.9	6.8	6.7	6.7	6.7	6.7	6.6	6.5	6.6	6.5	6.5	6.4	6.2			

