

屋内照明器具特性

品番 (品名)	NNCF44235 (J Y O U J I)									
光源	LED5000_85_3800 x1 3800.0 lm									
管理番号	K0190329 (0) DR 1									
BZ分類	BZ6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	19 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	81 %																																																						
保守率	良 中 否	0.83	0.6	51	38	30	24	48	37	29	24	44	34	27	23	40	32	26	21	18																																			
		0.81	0.8	60	47	39	33	57	46	38	32	52	42	36	30	47	39	33	29	25																																			
			1.0	66	54	46	39	63	52	44	38	57	48	41	36	52	45	39	34	30																																			
		0.77	1.25	71	60	52	46	68	58	51	45	62	54	47	42	57	50	44	40	35																																			
下方投影面積	c m ²	1.5	76	65	57	51	72	63	56	50	66	58	52	47	60	54	49	44	39																																				
		2.0	81	72	65	59	78	70	63	57	71	65	59	54	65	60	55	51	45																																				
取付高さ	器具間隔最大限		2.5	85	77	70	65	81	74	68	63	75	69	64	59	69	64	60	56	49																																			
	横方向 (A)	縦方向 (B)	3.0	88	80	74	69	84	78	72	67	77	72	67	63	71	67	63	60	53																																			
1.5m	1.9m	2.11m	4.0	91	85	80	75	87	82	77	73	81	76	73	69	75	71	68	65	58																																			
2	2.52	2.69	5.0	93	88	84	80	90	85	81	77	83	79	76	73	77	74	71	68	61																																			
2.5	3.13	3.28	7.0	96	92	88	85	92	89	86	83	86	83	80	78	80	77	75	73	65																																			
3	3.76	3.89	10.0	98	95	92	90	95	92	89	87	88	86	84	82	82	80	78	77	69																																			

