

屋内照明器具特性	
品番 (品名)	XFL312VZPJ
光源	LDL40S.N/14/26 x1 2600.0 1m
管理番号	K0189122(0)D 1
BZ分類	BZ3

器具効率	70%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	70%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.77	0.6	45	38	33	30	45	38	33	30	43	37	33	30	42	36	33	30	29
		0.72	0.8	52	46	41	38	51	45	41	38	50	44	40	37	48	43	40	37	36
			1.0	56	50	46	43	56	50	46	43	54	49	45	43	52	48	45	42	41
		0.68	1.25	60	55	51	48	59	54	50	47	57	53	50	47	56	52	49	47	45
下方投影面積	c m ²	1.5	62	58	54	51	62	57	54	51	60	56	53	50	58	55	52	50	48	
		2.0	66	62	58	56	65	61	58	55	63	60	57	55	61	58	56	54	53	
取付高さ	器具間隔最大限		2.5	68	64	61	59	67	64	61	59	65	62	60	58	63	61	59	57	56
	横方向 (A)	縦方向 (B)	3.0	69	66	64	61	68	65	63	61	66	64	62	60	64	62	61	59	58
1.5m	1.68m	2.06m	4.0	71	68	66	64	70	68	66	64	68	66	64	63	66	65	63	62	60
2	2.24	2.62	5.0	72	70	68	66	71	69	67	66	69	67	66	65	67	66	65	64	62
2.5	2.8	3.19	7.0	73	71	70	69	72	71	69	68	70	69	68	67	68	68	67	66	64
3	3.35	3.78	10.0	74	73	72	71	73	72	71	70	71	70	69	69	69	69	68	68	65

