

屋内照明器具特性	
品番 (品名)	NY Y 4 1 0 2 3
光源	LED 3 0 0 0 _ 7 0 _ 1 6 4 5 × 1 1 6 4 5 . 0 l m
管理番号	K 0 1 7 1 2 0 6 (0) DB 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		5 0 %																				
保守率		良 中 否	0 . 6 9	0 . 6	6 0	5 2	4 6	4 2	5 7	4 9	4 4	4 0	5 0	4 4	4 0	3 8	4 4	4 0	3 7	3 5	3 0	
			0 . 6 7	0 . 8	6 8	6 0	5 4	5 0	6 4	5 7	5 2	4 8	5 6	5 1	4 7	4 4	4 9	4 5	4 3	4 1	3 4	
			0 . 6 3	1 . 0	7 3	6 6	6 0	5 6	6 9	6 2	5 7	5 4	6 0	5 5	5 2	4 9	5 2	4 9	4 6	4 4	3 7	
				1 . 2 5	7 8	7 1	6 6	6 2	7 3	6 7	6 2	5 9	6 3	5 9	5 6	5 3	5 5	5 2	5 0	4 8	3 9	
下方投影面積		c m ²	1 . 5	8 1	7 5	7 0	6 6	7 6	7 0	6 6	6 3	6 6	6 2	5 9	5 7	5 7	5 4	5 2	5 0	4 1		
等価発光面積			c m ²	2 . 0	8 5	8 0	7 6	7 2	7 9	7 5	7 1	6 8	6 9	6 6	6 3	6 1	5 9	5 7	5 5	5 4	4 3	
取付高さ	器具間隔最大限		2 . 5	8 7	8 3	7 9	7 6	8 1	7 8	7 5	7 2	7 1	6 8	6 6	6 4	6 0	5 9	5 7	5 6	4 4		
	横方向 (A)	縦方向 (B)	3 . 0	8 9	8 5	8 2	7 9	8 3	8 0	7 7	7 5	7 2	7 0	6 8	6 6	6 1	6 0	5 9	5 8	4 5		
H m	0 . 6 6 H m	0 . 6 6 H m	4 . 0	9 1	8 8	8 5	8 3	8 5	8 3	8 0	7 8	7 4	7 2	7 0	6 9	6 3	6 2	6 1	6 0	4 6		
			5 . 0	9 2	9 0	8 8	8 6	8 6	8 4	8 2	8 1	7 5	7 3	7 2	7 1	6 4	6 3	6 2	6 1	4 7		
			7 . 0	9 4	9 2	9 0	8 9	8 8	8 6	8 5	8 3	7 6	7 5	7 4	7 3	6 4	6 4	6 3	6 3	4 8		
			1 0 . 0	9 5	9 4	9 2	9 1	8 9	8 8	8 6	8 6	7 7	7 6	7 5	7 4	6 5	6 5	6 4	6 4	4 8		

