

# 屋内照明器具特性

|         |                             |  |  |  |  |          |  |  |  |  |
|---------|-----------------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | XAS3311L                    |  |  |  |  |          |  |  |  |  |
| 光源      | LED2700_70_460 x2           |  |  |  |  | 460.0 lm |  |  |  |  |
| 管理番号    | K0170905(0)DB1              |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ3/2.8/BZ2/4.5/BZ3/6.0/BZ2 |  |  |  |  |          |  |  |  |  |

| 器具効率   | 100%    | 天井              | 80%  |               |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |     |
|--------|---------|-----------------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
|        |         |                 | 壁    | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |
| 上方光束   | 0%      |                 |      |               |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
| 下方光束   | 100%    |                 |      |               |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
|        |         | 反射率             |      |               |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
|        |         |                 | 天井   | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |    |    |    | 0%  |
|        |         |                 | 壁    | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |
|        |         |                 | 床    | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0%  |
|        |         |                 | 室指数  | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |
| 保守率    | 良       | 0.67            | 0.6  | 63            | 52  | 46  | 41  | 62  | 52  | 45  | 41  | 60  | 51  | 45  | 41  | 58  | 50 | 44 | 40 | 39  |
|        | 中       | 0.63            | 0.8  | 74            | 64  | 57  | 53  | 72  | 63  | 57  | 53  | 70  | 62  | 57  | 52  | 68  | 61 | 56 | 52 | 50  |
|        | 否       | 0.56            | 1.0  | 80            | 72  | 66  | 61  | 79  | 71  | 65  | 61  | 77  | 70  | 64  | 60  | 74  | 68 | 64 | 60 | 58  |
|        |         |                 | 1.25 | 86            | 79  | 73  | 69  | 85  | 78  | 72  | 68  | 82  | 76  | 72  | 68  | 80  | 75 | 71 | 67 | 65  |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5  | 90            | 83  | 78  | 74  | 88  | 82  | 77  | 73  | 86  | 81  | 76  | 73  | 83  | 79 | 75 | 72 | 70  |
|        | 等価発光面積  | cm <sup>2</sup> | 2.0  | 95            | 89  | 85  | 81  | 93  | 88  | 84  | 81  | 91  | 86  | 83  | 80  | 88  | 85 | 82 | 79 | 77  |
| 取付高さ   | 器具間隔最大限 |                 | 2.5  | 97            | 93  | 89  | 86  | 96  | 92  | 88  | 85  | 94  | 90  | 87  | 84  | 91  | 88 | 86 | 83 | 81  |
|        | 横方向 (A) | 縦方向 (B)         | 3.0  | 99            | 95  | 92  | 89  | 98  | 94  | 91  | 89  | 95  | 92  | 90  | 87  | 93  | 91 | 88 | 86 | 84  |
| Hm     | 1.22Hm  | 1.22Hm          | 4.0  | 102           | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 95  | 93  | 91  | 95  | 94 | 92 | 90 | 88  |
|        |         |                 | 5.0  | 103           | 101 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97  | 96  | 94  | 97  | 95 | 94 | 93 | 90  |
|        |         |                 | 7.0  | 105           | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 99  | 98  | 97  | 99  | 97 | 96 | 95 | 93  |
|        |         |                 | 10.0 | 106           | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99 | 98 | 97 | 95  |

