

# 屋内照明器具特性

品番 (品名)	S P L 5 4 2 9	
光源	LLD4000LCE1 ×4	845.0 l m
管理番号	K0183106 ( 0 ) DB 1	
B Z 分類	B Z 5	

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	76 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 ( X 0 . 0 1 )																				Z C M
保守率	良	0.67	0.6	43	34	28	24	42	34	28	24	41	33	28	24	39	32	27	24	22	
	中	0.63	0.8	51	42	36	32	50	42	36	32	48	41	36	32	46	40	35	32	30	
	否	0.56	1.0	56	48	42	38	55	47	42	38	53	46	41	37	51	45	41	37	35	
			1.25	61	53	48	44	59	53	47	43	57	51	47	43	55	50	46	43	41	
下方投影面積	c m <sup>2</sup>		1.5	64	57	52	48	63	56	52	48	60	55	51	47	58	54	50	47	45	
等価発光面積	c m <sup>2</sup>		2.0	68	63	58	54	67	62	58	54	65	60	56	53	62	59	56	53	51	
取付高さ	器具間隔最大限		2.5	71	66	62	59	70	65	61	58	67	64	60	58	65	62	59	57	55	
	横方向 ( A )	縦方向 ( B )	3.0	73	69	65	62	72	68	64	61	69	66	63	61	67	64	62	60	58	
H m	1.27 H m	1.27 H m	4.0	75	72	69	66	74	71	68	66	72	69	67	65	70	68	66	64	62	
			5.0	77	74	71	69	75	73	71	69	73	71	69	67	71	70	68	66	64	
			7.0	78	76	74	73	77	75	74	72	75	74	72	71	73	72	71	70	67	
			10.0	79	78	77	75	78	77	76	75	77	75	74	73	75	74	73	72	70	

