

屋内照明器具特性

品番 (品名)	S P L 5 4 2 9	
光源	LLD5010LCC1 ×4	1095.0 1m
管理番号	K0187252 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 2 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	98 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X 0.01)																			ZCM
保守率	良 0.67	0.6	83	77	73	70	82	76	73	70	81	76	72	70	79	75	72	70	68	
	中 0.63		88	83	79	76	87	82	79	76	86	81	78	76	84	80	77	75	74	
	否 0.56		92	87	83	80	91	86	83	80	89	85	82	79	87	84	81	79	77	
下方投影面積	c m ²	1.25	95	90	87	84	94	89	86	84	92	88	85	83	90	87	84	82	80	
		1.5	97	93	89	87	96	92	89	86	93	90	87	85	91	89	86	85	83	
等価発光面積	c m ²	2.0	99	96	93	91	98	95	92	90	96	93	91	89	93	91	89	88	86	
		2.5	101	98	95	93	100	97	95	93	97	95	93	91	95	93	91	90	88	
取付高さ	器具間隔最大限		3.0	102	99	97	95	101	98	96	94	98	96	94	93	96	94	93	89	
	横方向 (A)	縦方向 (B)	4.0	103	101	99	98	102	100	98	97	100	98	97	95	97	96	95	94	91
H m	0.81 H m	0.81 H m	5.0	104	103	101	100	103	101	100	99	100	99	98	97	98	97	96	95	92
			7.0	105	104	103	102	104	103	102	101	101	100	99	99	99	98	97	97	93
			10.0	106	105	104	103	105	104	103	102	102	101	101	100	99	99	98	98	95

