

# 屋内照明器具特性

品番 (品名)	SLB16781+SLK22012+SLK290	
光源	LLD3401LCB1 ×1	700.0 1 m
管理番号	K0193683 ( 0 ) DB 1	
BZ分類	BZ2 / 1.8 / BZ3 / 8.5 / BZ4	

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	9 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	82 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	60	51	45	41	58	50	45	41	56	49	44	41	53	47	43	40	38			
	中	0.6	0.8	68	60	54	50	66	59	53	49	63	57	52	49	60	55	51	48	45			
	否	0.56	1.0	73	65	60	56	71	64	59	55	68	62	57	54	65	60	56	53	50			
			1.25	77	70	65	61	75	69	64	60	72	66	62	59	68	64	61	58	55			
下方投影面積		cm <sup>2</sup>	1.5	80	74	69	65	78	72	68	64	74	70	66	63	71	67	64	61	58			
等価発光面積		cm <sup>2</sup>	2.0	84	79	74	71	82	77	73	70	78	74	71	68	74	71	69	66	63			
取付高さ	器具間隔最大限		2.5	86	82	78	75	84	80	77	74	80	77	74	72	77	74	72	69	66			
	横方向 (A)	縦方向 (B)	3.0	88	84	81	78	86	82	79	76	82	79	76	74	78	76	74	72	68			
H <sub>m</sub>	0.62 H <sub>m</sub>	0.62 H <sub>m</sub>	4.0	90	87	84	81	88	85	82	80	84	81	79	77	80	78	76	75	71			
			5.0	91	89	86	84	89	87	84	82	85	83	81	80	81	80	78	77	72			
			7.0	93	91	89	87	91	89	87	85	87	85	84	82	83	82	80	79	75			
			10.0	94	92	91	90	92	90	89	88	88	87	86	85	84	83	82	81	77			

