

屋内照明器具特性	
品番 (品名)	XAD1101LK
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0175548(0)DR1
BZ分類	BZ4/0.7/BZ3

器具効率	64%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	64%																																																						
保守率	良	0.67	0.6	3.9	3.2	2.7	2.4	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.5	3.0	2.6	2.4	2.3																																			
	中	0.63	0.8	4.6	3.9	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0																																			
	否	0.56	1.0	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.7	4.7	4.3	3.9	3.6	4.6	4.2	3.9	3.6	3.5																																			
			1.25	5.4	4.9	4.5	4.2	5.3	4.8	4.4	4.1	5.1	4.7	4.4	4.1	5.0	4.6	4.3	4.1	3.9																																			
下方投影面積		cm ²	1.5	5.6	5.2	4.8	4.5	5.5	5.1	4.8	4.5	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	4.3																																			
等価発光面積		cm ²	2.0	5.9	5.6	5.2	5.0	5.9	5.5	5.2	5.0	5.7	5.4	5.1	4.9	5.5	5.3	5.0	4.9	4.7																																			
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.3	6.0	5.8	5.5	5.3	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.2	5.0																																			
	横方向 (A)	縦方向 (B)	3.0	6.3	6.0	5.8	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.2																																			
Hm	1.25Hm	1.25Hm	4.0	6.4	6.2	6.0	5.8	6.3	6.1	6.0	5.8	6.2	6.0	5.9	5.7	6.0	5.9	5.8	5.6	5.5																																			
			5.0	6.5	6.4	6.2	6.0	6.4	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6																																			
			7.0	6.6	6.5	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	5.8																																			
			10.0	6.7	6.6	6.5	6.5	6.6	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.3	6.3	6.2	6.2	6.0																																			

