

屋内照明器具特性

| | | |
|---------|--------------------|----------|
| 品番 (品名) | XAS3381V | |
| 光源 | LED3500_70_1120 x1 | 1120.0lm |
| 管理番号 | K0171365(0)D 1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-----------------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|-----|----|----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 41% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 59% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | | | |
| 保守率 | 良 0.67 | 0.6 | 68 | 60 | 56 | 52 | 65 | 58 | 54 | 51 | 59 | 54 | 51 | 49 | 54 | 51 | 48 | 46 | 42 | |
| | 中 0.63 | | 0.8 | 75 | 67 | 63 | 59 | 71 | 65 | 61 | 58 | 64 | 60 | 57 | 54 | 58 | 55 | 53 | 51 | 46 |
| | 否 0.56 | | 1.0 | 79 | 72 | 68 | 64 | 75 | 69 | 65 | 62 | 68 | 64 | 61 | 58 | 61 | 58 | 56 | 54 | 48 |
| 下方投影面積 | cm ² | 1.25 | 83 | 77 | 72 | 69 | 78 | 73 | 70 | 67 | 71 | 67 | 64 | 62 | 63 | 61 | 59 | 57 | 50 | |
| | | 等価発光面積 | cm ² | 1.5 | 85 | 80 | 76 | 73 | 81 | 76 | 73 | 70 | 73 | 69 | 67 | 65 | 65 | 63 | 61 | 60 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 91 | 87 | 84 | 81 | 86 | 83 | 80 | 78 | 77 | 74 | 73 | 71 | 68 | 67 | 65 | 64 | 54 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 92 | 89 | 86 | 84 | 87 | 84 | 82 | 80 | 78 | 76 | 74 | 73 | 69 | 68 | 67 | 66 | 55 |
| Hm | 0.41Hm | 0.41Hm | 4.0 | 94 | 91 | 89 | 87 | 89 | 87 | 85 | 83 | 79 | 78 | 76 | 75 | 70 | 69 | 68 | 67 | 56 |
| | | | 5.0 | 95 | 93 | 91 | 89 | 90 | 88 | 86 | 85 | 80 | 79 | 78 | 77 | 71 | 70 | 69 | 68 | 57 |
| | | | 7.0 | 96 | 95 | 93 | 92 | 91 | 90 | 88 | 87 | 81 | 80 | 79 | 78 | 71 | 71 | 70 | 70 | 57 |
| | | | 10.0 | 97 | 96 | 95 | 94 | 92 | 91 | 90 | 89 | 82 | 81 | 80 | 80 | 72 | 71 | 71 | 71 | 58 |

