

屋内照明器具特性

品番 (品名)	XAS3391V	
光源	LED3500_70_1035 ×1	1035.0lm
管理番号	K0171366(0)D 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 44%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	56%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	67	59	54	50	63	57	52	49	57	52	49	47	52	48	46	44	40	
	中 0.63		0.8	73	66	61	57	69	63	59	56	62	58	55	52	56	53	51	49	43
	否 0.56		1.0	78	71	66	63	73	68	64	60	66	62	59	56	59	56	54	52	46
下方投影面積 等価発光面積	cm ²	1.25	81	75	71	67	77	72	68	65	69	65	62	60	61	58	57	55	47	
		1.5	84	79	74	71	79	75	71	68	71	67	65	63	62	60	59	57	49	
取付高さ	器具間隔最大限		2.5	90	86	83	80	84	81	79	76	75	72	71	69	66	64	63	51	
	横方向 (A)	縦方向 (B)	3.0	91	88	85	82	86	83	81	78	76	74	72	71	66	65	64	52	
Hm	0.41Hm	0.41Hm	4.0	93	90	88	86	88	85	83	82	77	76	74	73	67	67	66	53	
			5.0	94	92	90	88	89	87	85	84	78	77	76	75	68	67	67	53	
			7.0	95	94	92	91	90	88	87	86	79	78	77	76	69	68	68	54	
			10.0	96	95	94	93	91	90	89	88	80	79	78	78	69	69	69	54	

