

屋内照明器具特性

品番 (品名)	SLB16781+SLK22013+SLK290	
光源	LLD3401LCB1 ×1	700.0 lm
管理番号	K0192481(1)DR1	
BZ分類	BZ1	

器具効率	38%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	38%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	3.1	2.9	2.7	2.6	3.1	2.9	2.7	2.6	3.0	2.8	2.7	2.6	3.0	2.8	2.7	2.6	2.6			
	中	0.63	0.8	3.4	3.2	3.0	2.9	3.4	3.2	3.0	2.9	3.3	3.1	3.0	2.9	3.2	3.1	3.0	2.9	2.8			
	否	0.56	1.0	3.5	3.4	3.2	3.1	3.5	3.3	3.2	3.1	3.4	3.3	3.2	3.1	3.4	3.3	3.2	3.1	3.0			
			1.25	3.7	3.5	3.4	3.3	3.6	3.5	3.4	3.3	3.6	3.4	3.3	3.2	3.5	3.4	3.3	3.2	3.2			
下方投影面積	cm ²		1.5	3.7	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.4	3.6	3.5	3.4	3.3	3.3			
	等価発光面積		2.0	3.8	3.7	3.6	3.5	3.8	3.7	3.6	3.5	3.7	3.6	3.6	3.5	3.7	3.6	3.5	3.5	3.4			
取付高さ	器具間隔最大限		2.5	3.9	3.8	3.7	3.6	3.9	3.8	3.7	3.6	3.8	3.7	3.6	3.6	3.7	3.6	3.6	3.5	3.5			
	横方向 (A)	縦方向 (B)	3.0	3.9	3.8	3.8	3.7	3.9	3.8	3.7	3.7	3.8	3.8	3.7	3.6	3.7	3.7	3.6	3.6	3.5			
Hm	0.87Hm	0.86Hm	4.0	4.0	3.9	3.8	3.9	3.9	3.8	3.8	3.9	3.8	3.8	3.7	3.8	3.7	3.7	3.7	3.6				
			5.0	4.0	4.0	3.9	3.9	4.0	3.9	3.9	3.8	3.9	3.8	3.8	3.8	3.8	3.8	3.7	3.7	3.6			
			7.0	4.0	4.0	4.0	3.9	4.0	4.0	3.9	3.9	3.9	3.9	3.9	3.9	3.8	3.8	3.8	3.8	3.7			
			10.0	4.1	4.0	4.0	4.0	4.0	4.0	4.0	4.0	3.9	3.9	3.9	3.9	3.9	3.9	3.8	3.8	3.7			

