

# 屋内照明器具特性

品番 (品名)	SLB16781 + SLK22014 + SLK290	
光源	LLD2421LCB1 ×1	500.0 l m
管理番号	K0192486 (1) DR 1	
BZ分類	BZ1	

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %				
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10					
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %			
下方光束	57 %		床	10 %				10 %				10 %				10 %				0 %			
		室指数	照明率 ( X 0.01 )																				ZCM
保守率	良 0.67	0.6	51	49	47	46	51	49	47	46	50	48	47	46	50	48	47	46	45				
	中 0.63	0.8	54	52	50	49	54	51	50	49	53	51	50	49	52	51	49	49	48				
	否 0.56	1.0	56	54	52	51	55	53	52	51	54	53	52	51	54	52	51	50	50				
下方投影面積	c m <sup>2</sup>	1.25	57	55	54	53	57	55	54	53	56	54	53	52	55	54	53	52	51				
		1.5	58	56	55	54	57	56	55	54	56	55	54	53	56	55	54	53	52				
等価発光面積	c m <sup>2</sup>	2.0	59	58	57	56	58	57	56	55	57	56	56	55	56	56	55	54	53				
		2.5	60	58	58	57	59	58	57	56	58	57	56	56	57	56	56	55	54				
取付高さ	器具間隔最大限		3.0	60	59	58	58	59	59	58	57	58	58	57	57	57	57	56	55				
H m	横方向 (A)	縦方向 (B)	4.0	61	60	59	59	60	59	59	58	59	58	58	57	58	57	57	55				
	0.34 H m	0.35 H m	5.0	61	60	60	59	60	60	59	59	59	59	58	58	58	58	57	56				
			7.0	61	61	60	60	61	60	60	60	59	59	59	59	58	58	58	56				
			10.0	62	61	61	61	61	61	60	60	60	59	59	59	59	58	58	57				

