

# 屋内照明器具特性

品番 (品名)	SLB17079									
光源	LED2700_70_1885 x1					1885.0 lm				
管理番号	K0178694(0)DB1									
BZ分類	BZ4/6.0/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	8%																			
下方光束	92%																			
室指数	照明率 ( X0.01 )																ZCM			
保守率	良 中 否	0.63	0.6	60	49	42	37	58	48	41	36	55	46	40	36	52	45	39	35	33
		0.6	0.8	69	59	52	47	67	58	51	46	64	56	50	45	61	54	49	45	42
		0.56	1.0	75	66	59	54	73	65	58	53	70	62	57	52	66	60	55	51	48
			1.25	81	72	66	60	79	71	65	60	75	68	63	58	71	65	61	57	54
下方投影面積		cm <sup>2</sup>																		
等価発光面積		cm <sup>2</sup>																		
取付高さ	器具間隔最大限		2.5	92	87	82	78	90	85	80	77	86	82	78	74	82	78	75	72	68
	横方向 (A)	縦方向 (B)																		
1.5m	1.39m	2.06m	4.0	97	93	90	86	95	91	88	85	91	88	85	82	87	84	82	80	75
2	1.86	2.66	5.0	99	96	92	90	97	94	91	88	93	90	88	85	89	86	84	83	78
2.5	2.32	3.26	7.0	101	98	96	94	99	96	94	92	95	93	91	89	91	89	88	86	81
3	2.79	3.91	10.0	103	101	99	97	100	99	97	95	96	95	93	92	92	91	90	89	84

